

**EL.LI.COM**

Η επιλογή σου



TECHNICAL FEATURES

Polyamide 66 reinforced with 30% fiberglass

Self-extinguishing UL 94-V0


Working temperature: -40°C to +130°C**Continuous working temperature:** +125°C**Softening temperature:** +250°C**Glow wire test:** 960°C

Black colour


M6 screws for bar fastening included for PSP1000 and PSP1005

Protection screen fastening kit included for PSP1000 (cf. code DZP2000) and PSP1005


Direct fastening kit on DIN rail included for PSP1005




PSP 250



PSP 400



PSP 630T



PSP 630TN

REPARTITION SUPPORTS

Code	Reference		Type	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
PSP1000	PSP 250	8	T+N	150	54	15	130	-
PSP1005	PSP 400	2	T+N	216	117	34	200	-
PSP1010	PSP 630T	1	T	180	55	18	-	60
PSP1020	PSP 630TN	1	T+N	240	55	18	-	60



PROTECTION CAPS

Code	Reference		Type	A (mm)	B (mm)	C (mm)
PSP1015	PSP PRO 630T	1	for support PSP1010	185	36	23
PSP1025	PSP PRO 630TN	1	for support PSP1020	245	36	23

TEKNOLOGIA