

ET 35



Approvals



General Data

Type	ET 35
Wire Termination Technology	Screw Clamp
Ratings	35 sq mm/3 Nm
GTIN / Harmonize Custom Code	85389000
Standard Packing Qty (in No)	20
Country of Origin	India
Screw Size	M6

Dimensions & Weight

Height (mm)	63
Height (inches)	2.48
Width (mm)	58
Width (inches)	2.28
Thickness (mm)	16.5
Weight For Standard Packing Qty (Kg)	2.12

Material Data

Housing	PA 6,6
Standard Colour	Green-Yellow
Other Color Variants	No more colors available

Rated Conductor Size

Stranded Wire - min (sq mm)	6
Stranded Wire - max (sq mm)	35
Solid Wire - min (sq mm)	6
Solid Wire - max (sq mm)	35

Ratings - IEC

Standard	IEC 60947-7-2
Rated Voltage (V)	-
Rated Current (A)	-
Rated Cross Section (sq mm)	35
Short Time Withstand Current (kA)	4.20
Rated Impulse Withstand Voltage(kV)	-
Pollution Degree	III

Ratings-ATEX


Certificate No	-
Rated Current (A)	-
Rated Cross Section (sq mm)	35

Ratings-CSA

Rated Voltage (V)	-
Rated Current (A)	-
Wire Cross Section - min (AWG)	8

Wire Cross Section - max (AWG)	1
--------------------------------	---

Ratings-uL	
Rated Voltage (V)	-
Rated Current (A)	-
Conductor Size - min (AWG)	8
Conductor Size - max (AWG)	1

Accessories	
Partition Plate With Foot	
KBZF Height : 65 mm Width : 65 mm Thickness : 1.50 mm	
Protection Cover	
PCK3	
End Clamp	
SCUDD Height : 50 mm Width : 55.50 mm Thickness : 10 mm	

SCUSL Height : 41 mm Width : 47.50 mm Thickness : 8 mm	
Marking Label	
LABEL KN12	
Mounting Channel (Standard Lengths 300 mm, 500 mm, 1000 mm)	
CHK Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
CHKD Height : 15 mm Width : 35 mm Thickness : 1.50 mm	
CHKDS (Perforated) Height : 15 mm Width : 35 mm Thickness : 1.50 mm	

CHKS (Perforated) Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
CHS Height : 15 mm Width : 32 mm Thickness : 1.50 mm	
Support for Protection Cover	
UHDD Height : 74.50 mm Width : 55.82 mm Thickness : 1.50 mm	
Group Marking Holder	
GMH 10 Height : 51 mm Width : 41.50 mm Thickness : 10 mm	
GMH 20 Height : 51 mm Width : 41.50 mm Thickness : 20 mm	