


DST 4



Approvals



General Data

Type	DST 4
Wire Termination Technology	Spring Clamp
Ratings	800 V/32 A/4 sq mm
GTIN / Harmonize Custom Code	85389000
Standard Packing Qty (in No)	100
Country of Origin	India
Screw Size	NA

Dimensions & Weight

Height (mm)	33.50
Height (inches)	1.31
Width (mm)	59
Width (inches)	2.32
Thickness (mm)	6
Weight For Standard Packing Qty (Kg)	0.92

Material Data

Housing	PA 6,6
Standard Colour	Grey
Other Color Variants	Black, Blue, Green, Khakhi, Red, Yellow

Rated Conductor Size

Stranded Wire - min (sq mm)	0.5
Stranded Wire - max (sq mm)	4
Solid Wire - min (sq mm)	0.5
Solid Wire - max (sq mm)	4

Ratings - IEC

Standard	IEC 60947-7-1
Rated Voltage (V)	800
Rated Current (A)	32
Rated Cross Section (sq mm)	4
Short Time Withstand Current (kA)	0.72
Rated Impulse Withstand Voltage(kV)	8
Pollution Degree	-

Ratings-ATEX

Certificate No	500
Rated Current (A)	24
Rated Cross Section (sq mm)	4

Ratings-CSA

Rated Voltage (V)	600
Rated Current (A)	20
Wire Cross Section - min (AWG)	20

Wire Cross Section - max (AWG)	12
--------------------------------	----

Accessories

End Plate

DSEP4

Height : 27.5 mm
 Width : 59 mm
 Thickness : 2.50 mm



End Clamp

DCKN (Screwless - 35 mm Rail Mounted)

Height : 33 mm
 Width : 43.50 mm
 Thickness : 6 mm



DCKN10 (Screwless - 35 mm Rail Mounted)


Height : 33 mm
 Width : 43.50 mm
 Thickness : 10 mm




SCKN (35 mm Rail Mounted)

Height : 35.50 mm
 Width : 50.60 mm
 Thickness : 8 mm



SCUN (Universal Rail Mounted) Height : 35.50 mm Width : 50.60 mm Thickness : 9.50 mm	
Screwless Push-in type shorting link	
SSL 4 (2W)	
Marking Label	
LABEL KN5.5	
Group Marking Carrier	
DCKNMLH Height : 45.50 mm Width : 43.50 mm Thickness : 6 mm	
SCKNMLH Height : 45.50 mm Width : 48 mm Thickness : 8 mm	

SCUNMLH Height : 53.50 mm Width : 50.60 mm Thickness : 8 mm	
Mounting Channel (Standard Lengths 300 mm, 500 mm, 1000 mm)	
CHK Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
CHKD Height : 15 mm Width : 35 mm Thickness : 1.50 mm	
CHKDS (Perforated) Height : 15 mm Width : 35 mm Thickness : 1.50 mm	
CHKS (Perforated) Height : 7.5 mm Width : 35 mm Thickness : 1 mm	
Group Marking Holder	

