

# PG CABLE GRAND



**Material:** The main body make of nickel-plated brass, clamp pieces make of UL approved nylon PA, O-sealing make of nitrilebutadienerubber(NBR), weathering rubber(EPDM).

**Thread specification:** Metric, PG, G, NPT.

**Working temperature:** -40-°C to 100°C in static state, instantaneous heat resistance up to 120°C, -20°C to 80°C in dynamic state, instantaneous heat resistance up to 100°C.

**Protection class:** IP68( using O-sealing)

型號 Type	螺紋長度 Thread length L1	適用範圍 Entry range D1	螺紋寬度 Entry thread D2	電纜口尺寸 Cable gland dimensions L-L1	防鬆螺母尺寸 Locknut thread size D3
PG-07	8	3.5-3.6	7	23-8	16.5
PG-09	8	4.5-7	10.2	25-8	21.5
PG-11	8	5.5-10	11.5	27-8	25
PG-13.5	9	6-12	13.5	28-9	27
PG-16	10	10-14	16.5	30-10	30
PG-21	11	14-18	21	38-11	37.5
PG-29	11	18-25	27.5	42-11	47.5
PG-36	12	25-33	34.5	43-12	58
PG-42	13	30-38	40.5	48-13	65
PG-48	14	34-44	45.5	48-14	70
PG-63					