







IP68

IP69K



PAHS✓

REACH✓



- 材 料：黄铜镀镍
- 夹 紧 件：尼龙、阻燃等级V0，参照UL94
- 密 封 件：丁腈橡胶
- 防 护 等 级：IP68/IP69K(在夹紧范围内，并使用O型圈)
- 环 境 温 度：-40℃至+100℃
- UL/CSA证书号：E343544
- 应 用 特 点：适用于所有有防火，密封，固定，防滑要求的场合。

- Material: Brass with nickel plated (CuZn39Pb3, ASTM C37800, JIS C37800)
- Clamp jaw: Nylon PA,UL94-V0
- Sealing element: NBR
- Thread Type: Metric according to EN 60423
- Test Standard : EN50262 /EN62444 /UL514B
- Protection class: IP68/IP69K(the wire/cable is in clamping range,and assemble O-Ring on the groove)
- Range of temperature: -40℃ to +100℃
- UL/CSA Cert ID: E343544
- Application: apply to all fire prevention, sealing, fixed, the occasion of non-slip requirements

Brass cable gland 金属电缆接头

产品系列 Series	规格 Thread	电缆范围 Øk mm	螺纹长度 GL mm	本体高度 H mm	扳手直径 mm	螺纹外径 AG mm	开孔尺寸 Panel Mounting Hole mm	订货号 PartNo	数量/盒 Pcs/Box
DEK-UT-S	M12×1.5	3-6.5	8	18	14	12	12-12.3	UT.M120806	10
	M12×1.5	2-5	8	18	14	12	12-12.3	UT.M120805	10
	M16×1.5	4-8	8.2	20	17	16	16-16.3	UT.M160808	10
	M16×1.5	2-6	8.2	20	17	16	16-16.3	UT.M160806	10
	M20×1.5	6.7-12	9	22	22	20	20-20.3	UT.M200912	10
	M20×1.5	5-9	9	22	22	20	20-20.3	UT.M200909	10
	M25×1.5	13-18	10	25	30	25	25-25.3	UT.M251018	10
	M25×1.5	9-16	10	25	30	25	25-25.3	UT.M251016	10
	M32×1.5	18.5-25	12	30	40	32	32-32.3	UT.M321225	10
	M32×1.5	13-20	12	30	40	32	32-32.3	UT.M321220	10
	M40×1.5	23-32	14	35	50	40	40-40.3	UT.M401432	5
	M40×1.5	20-26	14	35	50	40	40-40.3	UT.M401426	5
	M50×1.5	32.7-38	14	38	57	50	50-50.3	UT.M501438	2
	M50×1.5	25-31	14	38	57	50	50-50.3	UT.M501431	2
	M63×1.5	37-44	16.6	40	64/68	63	63-63.3	UT.M631444	2
	M63×1.5	29-35	16.6	40	64/68	63	63-63.3	UT.M631435	2

