



- 材 料: 尼龙、VO等级, 参照UL94
- 密 封 件: 丁腈橡胶
- 防护等级: IP68/IP69K(在夹紧范围内, 并使用O型圈)
- 环境温度: 静态-40℃至100℃, 短时至120℃, 动态-20℃至80℃, 短时至100℃
- 供货颜色: ● 灰色 RAL7035 ● 黑色 RAL9005 其它颜色请询问
- Material: Nylon PA, UL94-V0
- Seal: NBR
- Protection class: IP68/IP69K (the wire/cable is in clamping range, and assemble O-Ring on the groove.)
- Temperature range: Static state: -40℃ to 100℃, short term to 120℃;
- Dynamic state: -20℃ to 80℃, short term to 100℃.
- Product Color: ● Gray RAL7035; ● Black RAL9005, Please inquire if the other color requested.

产品系列 Series	规格 Thread	电缆范围 Øk mm	螺纹长度 GL mm	本体高度 H mm	扳手直径 H mm	螺纹外径 AG mm	开孔尺寸 Panel Mounting Hole mm	订货号 PartNo		数量/袋 Qty/bag
								灰色 Grey	黑色 Black	
DEK-UK-S	M12 × 1.5	3-6.5	8	22	15	12	12-12.3	U.M1208060	U.M1208061	50
	M12 × 1.5	2-5	8	22	15	12	12-12.3	U.M1208050	U.M1208051	50
	M16 × 1.5	4-8	8.2	24	19	16	16-16.3	U.M1608080	U.M1608081	50
	M16 × 1.5	2-6	8.2	24	19	16	16-16.3	U.M1608060	U.M1608061	50
	M20 × 1.5	6.7-12	9	27	24	20	20-20.3	U.M2009120	U.M2009121	50
	M20 × 1.5	5-9	9	27	24	20	20-20.3	U.M2009090	U.M2009091	50
	M25 × 1.5	13-18	10	35	33	25	25-25.3	U.M2510180	U.M2510181	50
	M25 × 1.5	9-16	10	35	33	25	25-25.3	U.M2510160	U.M2510161	50
	M32 × 1.5	18.5-25	12	40	42	32	32-32.3	U.M3212250	U.M3212251	10
	M32 × 1.5	13-20	12	40	42	32	32-32.3	U.M3212200	U.M3212201	10
	M40 × 1.5	23-32	14	48	53	40	40-40.3	U.M4014320	U.M4014321	10
	M40 × 1.5	20-26	14	48	53	40	40-40.3	U.M4014260	U.M4014261	10
	M50 × 1.5	32.7-38	14	50	60	50	50-50.3	U.M5014380	U.M5014381	10
	M50 × 1.5	25-31	14	50	60	50	50-50.3	U.M5014310	U.M5014311	10
	M63 × 1.5	37-44	16.6	51	65/68	63	63-63.3	U.M6316440	U.M6316441	10
	M63 × 1.5	29-35	16.6	51	65/68	63	63-63.3	U.M6316350	U.M6316351	10

光接电缆
CABLE GLANDS

