


Earthing Braids in Tinned Copper

Flat Tinned Copper Earthing Braids with cross section $6 \text{ mm}^2 \div 100 \text{ mm}^2$ and length from 150 mm to 300 mm.

Technical Features

- Tinned Copper CU-ETP UNI 5649-71
- Standard wire $\varnothing 0,20 \text{ mm}$ ($\varnothing 0,15 \text{ mm}$ for cross sections. 6 and 10 mm^2)

Flat Tinned Copper Braids - References and Dimensions



Code	Reference		Weight kg	Current A	Sez. mm^2	Thickness mm	L mm	A mm	B mm	$\varnothing D$ mm
TMS1000	TMS 6-150-6	10	0,010	55	6	2,3	150	12	12	6,5
TMS1005	TMS 6-200-6	10	0,013	55	6	2,3	200	12	12	6,5
TMS1010	TMS 10-150-8	10	0,021	85	10	2,8	150	17	22	8,5
TMS1015	TMS 10-200-8	10	0,025	85	10	2,8	200	17	22	8,5
TMS1020	TMS 10-250-8	10	0,029	85	10	2,8	250	17	22	8,5
TMS1025	TMS 10-300-8	10	0,033	85	10	2,8	300	17	22	8,5
TMS1030	TMS 16-100-8	10	0,023	120	16	3,1	100	17	22	8,5
TMS1035	TMS 16-150-8	10	0,030	120	16	3,1	150	17	22	8,5
TMS1040	TMS 16-200-8	10	0,037	120	16	3,1	200	17	22	8,5
TMS1045	TMS 16-250-8	10	0,046	120	16	3,1	250	17	22	8,5
TMS1050	TMS 16-300-8	10	0,054	120	16	3,1	300	17	22	8,5
TMS1055	TMS 25-150-10	10	0,048	150	25	3,2	150	21	23	10,5
TMS1060	TMS 25-200-10	10	0,059	150	25	3,2	200	21	23	10,5
TMS1065	TMS 25-250-10	10	0,072	150	25	3,2	250	21	23	10,5
TMS1070	TMS 25-300-10	10	0,084	150	25	3,2	300	21	23	10,5
TMS1075	TMS 35-150-10	10	0,061	195	35	3,5	150	21	23	10,5
TMS1080	TMS 35-200-10	10	0,077	195	35	3,5	200	21	23	10,5
TMS1085	TMS 35-250-10	10	0,097	195	35	3,5	250	21	23	10,5
TMS1090	TMS 35-300-10	10	0,110	195	35	3,5	300	21	23	10,5
TMS1095	TMS 50-100-10	10	0,080	250	50	4,8	100	25	25	10,5
TMS1100	TMS 50-150-10	10	0,095	250	50	4,8	150	25	25	10,5
TMS1105	TMS 50-200-10	10	0,129	250	50	4,8	200	25	25	10,5
TMS1110	TMS 50-250-10	10	0,143	250	50	4,8	250	25	25	10,5
TMS1115	TMS 50-300-10	10	0,179	250	50	4,8	300	25	25	10,5
TMS1120	TMS 75-200-10	10	0,185	330	75	5,5	200	30	30	10,5
TMS1125	TMS 75-250-10	10	0,225	330	75	5,5	250	30	30	10,5
TMS1130	TMS 75-300-10	10	0,265	330	75	5,5	300	30	30	10,5
TMS1135	TMS 100-200-12	10	0,250	370	100	6,5	200	30	30	12,5
TMS1140	TMS 100-250-12	10	0,300	370	100	6,5	250	30	30	12,5
TMS1145	TMS 100-300-12	10	0,475	370	100	6,5	300	30	30	12,5