



XG003N / XG004N Neutral type Earth type

Plastic base : PC

Insert : Brass

Screw : Iron , zinc plated

Working Temperature:-35°C to 120°C

Color : blue and green as standard

\*we can supply any size brass bar according to customer require \*OEM service

Item No.	Spec. WxH - hole	Cable hole diameter(mm)	Screw size	Installation (mm)		Overall(mm)		current
				L	L1xW	Height		
XG003N XG003	6x9-4	Ø6	M4x8	48.2	59.2x11.2	29	30A	
	6x9-6	Ø6	M4x8	65.4	76.4x11.2			
	6x9-8	Ø6	M4x8	82.6	93.6x11.2			
	6x9-10	Ø6	M4x8	99.8	110.8x11.2			
	6x9-12	Ø6	M4x8	117	128x11.2			
XG004N XG004	8x12-4	Ø7	M5x10	48.2	59.2x12.5	32	60A	
	8x12-6	Ø7	M5x10	65.4	76.4x12.5			
	8x12-8	Ø7	M5x10	82.6	93.6x12.5			
	8x12-10	Ø7	M5x10	99.8	110.8x12.5			
	8x1-12	Ø7	M5x10	117	128x12.5			
XG005	5.3x10-5	Ø7	M5x10	56.5	65.1x10	27.8	80-100A	
	5.3x10-7	Ø7	M5x10	73.5	83.8x10	27.8		
	5.3x10-10	Ø7	M5x10	98.5	107.5x10	27.8		
	5.3x10-12	Ø7	M5x10	113.5	126.5x10	27.8		

