

延时断开单元

Delay operation unit

延时装置 Delayed Unit



型号 Type	延迟 Delay	时间 Time	辅助触点 Auxiliary contact	适用接触器 Suit for contactor
UT-0N	接通延时 Making delay	0.1~3 sec	1NO 1NC	UKC1-9~UKC1-85
UT-1N		0.1~30 sec		
UT-2N		10~180 sec		
UT-0F	断开延时 Breaking delay	0.1~3 sec		
UT-1F		0.1~30 sec		
UT-2F		10~180 sec		

参数 Parameter		型号 Model	空气延时头 Air delay contact
额定绝缘电压(V) Rated insulation voltage			660
额定工作电压(V) Rated working voltage			660
约定发热电流(A) Preset heating current			10
额定工作电流(A) (电感负载) Rated opreating current	AC	110V	5
		220V	3
	DC	110V	0.5
		220V	0.3
最小负载(可靠工作) Min. Load			0.6VA(6V/10mAC 以上 above)
最高操作频率 Max. opreating frequency			10800h
寿命 Life	机械 Mechanical		1000万次以上 10 million times above
	电气 Electric		120万次 1.2 million times
符合标准 Conforms Standard			GB-14048.4
海拔 Altitude			不超过2000米 Not exceed 2000m
环境温度℃ Ambient temperature			-25—+55
安装条件 Installing condition			可与垂直面倾斜 ±30° Can be ±30° from the vertical plane
接线端可连接导线 Wiring terminal can be connected with conductor			1(或)2根软(或硬)线 1.5mm ² —2.5mm ² 1(or) 2 flexible (or hard) cords 1.5mm ² —2.5mm ²
绝缘电阻MΩ Insulation resistance			10
耐压(AC) Resistance voltage			2500V:1分钟(min)
保存温度 Keeping temperature			-60—+80
相对湿度 Relative humidity			45%—85%
延时重复误差 Time delay repetitive error			(± 3%)
延时稳定误差 Time delay stabilized error			(± 20%)
温度误差 Temperature error			(± 0.3℃)
复位时间 Reset time			0.5秒以下 0.5s below