



CD60 Aluminium electrolytic capacitor (Start Capacitor)

CD60 aluminium electrolytic capacitor widely used to heat pump, water pump, air conditioner, freezers and refrigerators, etc. Apply to single phase AC motor starting , provide higher torque.

Rating capacity	Rating Voltage	Testing voltage	Insulation resistance	Working Temp.	Loss Tangent	Frequency
25-1500UF	110-330VAC	T-T: 1.2time/2S T-C:2000VAC,10S	T-T \geq 3000M. Ω μ f	-10 $^{\circ}$ C-55 $^{\circ}$ C	\leq 0.15 20 $^{\circ}$ C (100HZ)	50/60Hz
Durability:	55 $^{\circ}$ C constant temperature, <165V, 1s energizing after 59s off, accumulative total 30000times. 55 $^{\circ}$ C constant temperature, <330V, 1s energizing after 59s off, accumulative total 15000times.					

容量 Capacitance	125VAC		250VAC		330vac	
	D(mm)	H (mm)	D(mm)	H (mm)	D(mm)	H (mm)
50 MFD	34	60	34	60		
75 MFD	34	60	34	60		
100 MFD	34	60	34	80		
150 MFD	34	80	45	92		
200 MFD	34	80	45	92		
250 MFD	42	80	50	100		
300 MFD	45	80	50	100		
350 MFD	45	92	50	100		
400 MFD	45	92	50	100		
500 MFD	50	100	50	100		