

# Accessories for installation

# CAMALEONTE

# TECHNICAL INFORMATION

Series of products in spray package designed to satisfy the different needs of installation and of the maintenance of electromechanical , electrical and electronic equipment.

- Container under pressure. Keep away from sunlight and do not expose to temperature exceeding 50° C. Do not perforate or burn even after use.
- Do not spray the product onto flames or red hot objects.
- Keep away from sources of ignition. Do not smoke
- Keep away from children
- Do not breathe gas/fume/vapour/aerosol.
- Take precautionary measures against static discharges
- Use only in well ventilated place



| Code       | Model | Description                                  | Format (ml) |
|------------|-------|--|-------------|
| VE491700   | C01   | Unblocker - Lubricant - Waterproof - Cleaner | 400         |
| VE492500   | C02   | Cleaner - Sanitizer for air conditioners     | 400         |
| VJ90280000 | C03   | Compressed air                               | 400         |
| VJ90020000 | C04   | Clean dry contacts                           | 200         |
| VJ90100000 | C05   | Lubricating contact cleaner                  | 200         |
| VE494100   | C06   | Universal lubricant                          | 400         |
| VE493300   | C07   | Silicone based oil -Lubricant                | 400         |
| VE495800   | C08   | Professional zinc 98%                        | 400         |
| VE496600   | C09   | Removes silicone, glue, paint                | 200         |
| VE500500   | C10/R | Marker (red)                                 | 400         |
| VE499000   | C10/G | Marker (yellow)                              | 400         |
| VE498200   | C10/B | Marker (blue)                                | 400         |
| VE502100   | C10/N | Marker (black)                               | 400         |

## C01 UNBLOCKER-LUBRICANT-WATERPROOF-CLEANER

Penetrates attacking rust and any other type of oxidation by unlocking the rusted, blocked or frozen parts.  
Forms over time a protective film against water, ice, humidity and oxidation.



H222 - H229 - H315 - H336 - H411  
P210 - P211 - P251 - P264 - P280 - P304+P340 - P312 - P410+P412

## C02 CLEANER- SANITIZER FOR AIR CONDITIONERS

Sanitizing, specific product for cleaning civil and auto air-conditioning systems.



H222 - H229 - H319  
P210 - P211 - P251 - P264 - P280 - P305+P351+P338 - P337+P313 - P410

## C03 COMPRESSED AIR

Used for PC keyboards, printers, videos, electronic components, boiler burners to remove dust from small areas. To clean holes made in cement, or drain pipes etc.



H222 - H229  
P210 - P211 - P251 - P410+P412

## C04 CLEAN DRY CONTACTS

Dielectric up to 50000 volts.  
Cleans and deoxidizes electrical contacts, circuits and boards. Does not damage paints or plastic surfaces.  
Dries immediately.



H222 - H229 - H319  
P101 - P102 - P210 - P211 - P251 - P264 - P280 - P305+P351+P338 - P337+P313 - P410+P412

## C05 LUBRICATING CONTACT CLEANER

Dielectric up to 50000 volts.  
Cleans and deoxidizes electrical contacts, circuits and boards. Does not damage paints or plastic surfaces.  
Leaves a light protective film.



H222 - H229 - H319 - P336  
P210 - P211 - P251 - P264 - P280 - P304+P340 - P312 - P410+P412

## C06 UNIVERSAL LUBRICANT

Resistant to temperatures up to 300°C and allows long intervals between a lubrication and the other one.  
Assures a clean lubrication, anti-adhesive for dust and resistant to water.  
Does not damage the o-rings.



H222 - H229 - H411  
P210 - P211 - P251 - P273 - P391- P410+P412

## C07 SILICONE BASED OIL – LUBRICANT

Excellent anti-creaking effect.  
Creates a water-repellent and antioxidant protection on metals, steel, rubberized fabrics, etc..  
It is odourless and colourless, it preserves both at low temperatures (-38°C) and at high temperatures (+270°C). Polishes any material made of rubber, plastic, skin, wood, etc...



H222 - H229  
P210 - P211 - P251 - P410+P412

## C08 PROFESSIONAL ZINC 98%

Cold galvanizing for quick drying to protect against oxidation and rust.  
Zinc 98% assures brilliant coverage over time, dries quickly and does not wipe.  
The treated surface can be painted



H222 - H229 - H315 - H319 - H411  
P210 - P211 - P251 - P280 - P303+P352 - P332+P313 - P410+P412

## C09 REMOVES SILICONE, GLUE, PAINT

Breaks down silicon inks, tar, plants resins, glues, mastics and cuts off labels of all types



H222 - H229 - H315 - H336 - H410  
P210 - P211 - P251 - P264 - P280 - P304+P340 - P312 - P410+P412

## C10 MARKER (RED), (YELLOW), (BLUE), (BLACK)

100% ACRYLIC line marking paint for horizontal and vertical applications. Indicated for factories, indications of various kinds, industrial floors, on cement, on sand etc...



H222+H229 - H319 - H336  
P101 - P102 - P103 - P210 - P211 - P251 - P271 - P405 - P410+P412 - P501

**H222** Extremely flammable aerosol. - **H222+H229** Extremely flammable aerosol. Pressurized container: may burst if heated. - **H229** Pressurized container: may burst if heated. - **H315** Causes skin irritation. - **H319** Causes serious eye irritation. - **H336** May cause drowsiness or dizziness. - **H410** Very toxic to aquatic life with long lasting effects. - **H411** Toxic to aquatic life with long lasting effects.  
**P101** If medical advice is needed, have product container or label at hand - **P102** Keep out of reach of children. - **P103** Read label before use. - **P210** Keep away from heat/sparks/open flames/hot surfaces. No smoking. - **P211** Do not spray on an open flame or other ignition source. - **P251** Pressurized container: do not pierce or burn, even after use. - **P264** Wash . . . thoroughly after handling - **P271** Use only outdoors or in a well-ventilated area. - **P273** Avoid release to the environment. - **P280** Wear protective gloves / protective clothing / eye protection / face protection. - **P302+P352** IF ON SKIN: Wash with plenty of soap and water. - **P304+P340** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - **P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. - **P312** Call a POISON CENTER or doctor/physician if you feel unwell. - **P332+P313** If skin irritation occurs: Get medical advice/attention. - **P337+P313** If eye irritation persists: Get medical advice/attention. - **P391** Collect spillage. - **P405** Store locked up. - **P410+P412** Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F. - **P501** Dispose of contents/container in accordance with applicable regulations.