



# 340/D

## Sirena elettromeccanica di grande potenza | Electromechanical siren of great power



Questa sirena di grande potenza acustica, omnidirezionale, è realizzata in fusioni di alluminio. Adatta per installazioni industriali o sistemi di allertamento in zone estese. E' una sirena particolarmente protetta contro gli agenti atmosferici. Questo è il modello più piccolo della serie con un motore da 1 Hp, udibile in campo aperto fino a 1000m; motore trifase.



This siren of great acoustic power, omnidirectional, is made of cast aluminum. Suitable for industrial installations or early warning systems in large areas. Is a siren special protection against the elements. This is the smallest model of the series with a 1 Hp motor, audible in the open field up to 1000m; three-phase motor.

### GENERALI | GENERAL FEATURES

Modello	Model	Trifase   Three phase
Codice	Part Number	05.28.001B
Servizio	Service	Continuo   Continuous

### SUONO | SOUND

Livello	Level	123 dB /1m
Tipo	Type	Continuo   Continuous
Frequenza	Frequency	515Hz
Tempo accelerazione	Acceleration time	6s

### ALIMENTAZIONE | POWER SUPPLY

Tensione nominale	Voltage Rating	230V 400V
Potenza nominale	Rated	0,74kW (1Hp)
Frequenza	Frequency	50 Hz
Corrente media	Average Current	3.5A
Corrente massima	Maximum Current	5A
N° giri motore	RPM	2810
Cos φ	Cos φ	0.82
Classe isolamento	Isolation Class	F

### MECCANICHE | MECHANICAL

Materiali costruttivi	Building materials	Alluminio   Aluminum
Peso	Weight	23 kg
Ingombro massimo	Maximum Size	430x560mm

### AMBIENTE | ENVIRONMENT

Temperatura esercizio	Operating Temperature	-20 ÷ + 40 °C
N° finestre	Windows N°	11
Grado IP motore	Engine IP Degree	55
Grado IP sirena	FanIP Degree	25

### OMOLOGAZIONI | APPROVAL

Europa	Europe	CE
--------	--------	----