



MINIWATT

Sirena elettromeccanica piccola |
Small electromechanical siren



Dimensioni ridottissime, eccezionale resa acustica e minimo consumo sono le caratteristiche principale delle sirene serie Miniwatt.
Indispensabili ovunque si richiedano eccellenti e sicure prestazioni sonore ed l'eventualità di dover nascondere la sirena.
Trovano ideale applicazione in impianti antifurto, quadri di comando, segnali di emergenza in generale.



Small size, exceptional acoustic performance and minimum power consumption are the main features of the sirens Miniwatt. Indispensable wherever they require excellent sonic performance and secure and the possibility of having to hide the siren. Finds its ideal application in alarm systems, control panels, emergency signals in general.

GENERALI | GENERAL FEATURES

Modello	Model	Miniwatt 12v ac/dc	Miniwatt 24V ac/dc	Miniwatt 230Vac/dc
Codice	Part Number	14.42.001C	14.43.001C	14.46.001C
Servizio	Service	15 min	15 min	15 min

SUONO | SIREN

Livello	Level	98 dB@1m	103 dB@1m
Tipo	Type	Continuo Continuous	
Frequenza	Frequency	1000Hz	1500Hz

ALIMENTAZIONE | POWER SUPPLY

Tensione nominale	Voltage Rating	12V	24V	230V
Potenza nominale	Rated	10W	10W	42W
Frequenza	Frequency	dc - 60Hz	dc - 60 Hz	dc - 60Hz
Corrente media	Average Current	0.83A	0.41A	0.20A
Classe isolamento	Isolation Class	E	E	F

MECCANICHE | MECHANICAL

Materiali costruttivi	Building materials	ABS	
Peso	Weight	19g	390g
Ingombro massimo	Maximum Size	90Øx80mm	90Øx130mm

AMBIENTE | ENVIRONMENT

Temperatura esercizio	Operating Temperature	-20 ÷ 40°C
Grado IP motore	Engine IP Degree	44
Grado IP sirena	Fan IP degree	14

OMOLOGAZIONI | APPROVAL

Europa	Europe	CE
--------	--------	----